

Granville FS-R 5W/30

1 Litre, 5 Litre, 20 Litre & 205 Litre

PRODUCT DESCRIPTION

Granville FS-R 5W/30 is formulated using the very latest advanced additive technology and base oils. Manufactured to meet the latest performance demands of certain Renault vehicles requiring a low SAPs (sulphated ash, phosphorous and sulphur) content. Suitable for engines with diesel particulate filters fitted where this grade and specification is required.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C4

Renault: RN0720

MB: 226.51



* Image for illustrative purposes only.

PRODUCT BENEFITS

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

PRODUCT USAGE

For engines where this specification lubricant is required.

DIRECTIONS FOR USE

As recommended by the engine manufacturer.

STORAGE INSTRUCTIONS

Store Upright and sealed in a cool dry place, out of the reach of children.

| SIZE | PART NO | BARCODE |
|-----------|---------|---------------|
| 1 Litre | 0568 | 5020618005681 |
| 5 Litre | 0569 | 5020618005698 |
| 20 Litre | 0565 | 5020618005650 |
| 205 Litre | 0571 | 5020618005711 |



Granville FS-R 5W/30

1 Litre, 5 Litre, 20 Litre & 205 Litre

SHELF LIFE

5 years from date of manufacture.

| | |
|--------------------------------|----------------------|
| Appearance | : Amber liquid |
| Odour | : Characteristic |
| Solubility | : Insoluble in water |
| Percentage of Base Oil | : Less Than 80% |
| Percentage of Biodiesel | : Nil |

| Test | Method | Unit | Min. | Max. | Typical |
|----------------------------|------------|--------------------|------|-------|---------|
| Viscosity, Kinematic 100°C | ASTM D445 | mm ² /s | 9.3 | <12.5 | 12.3 |
| Viscosity, CCS -30°C | ASTM D4684 | mPa.s | | 6600 | |
| Total Base Number | ASTM D2896 | mg KOH/g | 6 | | 8.5 |
| HTHS Viscosity | ASTM D4683 | mPa.s | 3.5 | | |
| NOACK Volatility | ASTM D5800 | % | | 11 | |
| Viscosity, Kinematic 40°C | ASTM D445 | mm ² /s | | | 72.4 |
| Density | ASTM D792 | @ 15°C | | | 0.85 |

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

